

## PAN MIXER

# DZ 120V

### The classic

The most popular of our high-performance pan mixers offers impressive functions in both a stationary and mobile design. The special feet and the installed toggle lever mechanism provide safe positioning, and the pneumatic tyres ensure optimum mobility.

A particularly long lifespan and robustness are guaranteed by the drum cladding made of 5 mm highly wear-resistant steel and the solid underframe.

The maintenance-free gears and the adjustable mixing unit parts made of Hardox steel ensure excellent mixing results for fine and coarse grained mixtures with a grain size of up to 32mm. Almost all materials can be mixed using this universal mixing unit without an additional special mixing unit.

**Quick drainage is carried out via a segmental valve in the base of the drum.**

Our CE-compliant high-performance pan mixers impress thanks to state-of-the-art, extremely robust construction and special safety devices, such as the hinged protective grid with linked limit switch or the drainage protection grid.

	DZ 120V MOBILE	DZ 120V STATIONARY
<b>Item no.</b>	10727	09298
<b>Motor</b>	400V, 4.00kW	400V, 4.00kW
<b>Gearbox</b>	61 1/2/min	61 1/2/min
<b>Drum capacity</b>	196l	196l
<b>Mixing amount</b>	120l	120l
<b>Overall height ready to be moved</b>	1295 mm	-
<b>Overall height ready for mixing</b>	1325 mm	1315 mm
<b>Overall width</b>	935 mm	965 mm
<b>Overall length</b>	1685 mm	960 mm
<b>Drum diameter</b>	796 mm	796 mm
<b>Drum height</b>	400 mm	400 mm
<b>Filling height</b>	1325 mm	1315 mm
<b>Drainage height</b>	630 mm	630 mm
<b>Weight</b>	272 kg	277 kg
<b>Paintwork</b>	RAL 1013	RAL 1013
<b>Tyres</b>	Pneumatic tyres	-
<b>Miscellaneous</b>	Hinged protective grid	Hinged protective grid



